



CHRYSO[®] Infini-Tec

Anti-stick treatment for ready-mix drums

Long-lasting efficacy

Description

CHRYSO[®] Infini-Tec is a new generation anti-stick treatment which molecular design is 100 times more powerful than Teflon[®].

CHRYSO[®] Infini-Tec bonds with composite or steel to create a barrier that will not allow concrete to stick to the internal walls and fins of the drum.

CHRYSO[®] Infini-Tec adheres to the interior surfaces of the drum, hopper and chutes, and will not break down with any mix design.

CHRYSO[®] Infini-Tec lab results show that it lasts up to 1500m³ of delivered concrete and with the field results showing product performance still performing well after 1000m³.

CHRYSO[®] Infini-Tec has no impact on any compressive tests of concrete results.

Characteristics

- Nature: liquid
- Colour: milky white
- Density: 1.08

Packaging

Jerrycans: 5 L

Application

Areas of application

- Long lasting anti-stick treatment for drums.

Method of use

Dosage rate: approx. 1L for 1m³ to be treated.

CHRYSO[®] Infini-Tec must be applied onto a clean, dry surface without any coating or paint. A clean, dry drum is required for a successful application. Any water inside the drum will result in product failure.

CHRYSO[®] Infini-Tec can be sprayed, mopped or sponged.

CHRYSO[®] Infini-Tec must be allowed to properly dry: a minimum of 12 hours should be allowed. Any water entering the drum during this period will ruin the application.

Precautions

- Store away from frost.
- Shelf life: 12 months.

CHRYSO[®] Infini-Tec

CHRYSO

LA CHIMIE AU SERVICE DES
MATÉRIAUX DE CONSTRUCTION

Anti-stick treatment for ready-mix drums Long-lasting efficacy



Safety

This product is classified as "harmless".
In case of exposure, it is recommended to wear your protective equipment.

Before use, refer to the safety data sheet on our internet site www.chryso.com

The information contained in this document is given to the best of our knowledge and the results from extensive testing. However, it cannot, under any circumstances be considered as a warranty involving our liability in case of misuse. Tests should be carried out before any use of the product to ensure that the methods and conditions of use of the product are satisfactory. Our specialists are at the disposal of the users in order to help them with any problem encountered.

"Please enquire for the latest update"

Last update: 05/10